

FUJI-509F 3hr Fast Ni-MH/Ni-CD AA/AAA Charger



MAIN ADVANTAGES:

Intelligent & Smart Charger
2 LEDs Indicator
Individual Fast Charger
Absolutely Safe & Smart
100V-240V World Wide Voltage

MAIN FEATURES:

4 Individual Charging Channels
Super Quick Charger
5-Level Charge Protection
-Delta V/0 Delta V cut off
Timer Control Protection (7.5 Hours)
Reverse Polarity Protection
Over Current and Short Circuit Protection
Defective and Non-rechargeable battery detection

Low Current Leakage Minimizes loss of capacity and maintains charging of battery by Controlling Current Leakage
2 LED indicate battery charging status
Trickle Charge to Maintain Battery Charge
Worldwide Voltage 100V-240V
Battery Rescue Function
Pulse and Series Charging Technology for Fast and Efficient Charging
Powered by AC Outlet

SPECIFICATIOINS:

Export packing information

PCS/Carton	35PCS/CARTON
Carton Dimension	0.53*0.33*0.36M
Carton CBM	0.062CBM
G.W./Carton	7.26KGS

Technical Characteristics

Charger
Input: 100V-240V AC, 50/60Hz, 10W
Charging current: AA×2 650~800mA ; AA×4 350~450mA (average current)
AAA×2 350~450mA ; AAA×4 250~375mA (average current)

Environmental Condition

Ambient Temperature	0°C to 40°C/ Best at 25±2°C
Storage temperature	-20°C to 60°C/ Best at 25±5°C
Humidity	5% to 85%/ non condensing

Charging Times

Battery Type	Battery Capacity	Approximate Charging Time	
		1-2PCS	3-4PCS
Ni-MH/Ni-Cd AA(R6)	1800mAh	3.5hrs	6.5hrs
Ni-MH/Ni-Cd AA(R6)	2500mAh	4.2hrs	8.2hrs
Ni-MH/Ni-Cd AAA(R03)	800mAh	1.4hrs	2.7hrs

*When the batteries are fully charged, the charger will automatically switch to a minimum maintenance charge if the batteries are not immediately removed from the unit.

*Charge time stated is for a full charge on fully discharged batteries.