

FUJI-200S Standard Ni-MH/Ni-CD AA/AAA/9V Battery Charger



MAIN ADVANTAGES:

- Fashionable Image Design
- Plug in charger
- 2 LEDs Indicator
- Safety Timer Protection

MAIN FEATURES:

- Charge 2/4PCS Ni-MH/Ni-CD AA/AAA or 1-2PCS Ni-MH/Ni-CD 9V Batteries
- Low charging current will improve the life cycle of batteries
- Timer protection can control the maximum charging time to avoid overcharging
- Reverse Polarity Protection

SPECIFICATION

Export packing information

PCS/Carton	15PCS
Carton Dimension	0.42*0.32*0.24M
Carton CBM	0.032CBM
N.W./Carton	
G.W./Carton	6.5KGS

Technical Characteristics

- Powered by AC Household Outlet
- Input: 100V-240V AC, 50/60Hz, 5W
- Charging current: AA 200mA-300mA; AAA:150-200Ma, 6F22 25mA

Environmental Conditions

Ambient Temperature	0°C to 40°C/ Best at 25±2°C
Storage temperature	-20°C to 60°C/ Best at 25±5°C
Humidity	5% to 85%/ non condensing

Charging Time

Battery Type	Battery Capacity	Approximate Charging time
R03/AAA Ni-MH	900mAh	6.0hrs
R03/AAA Ni-MH	800mAh	5.5hrs
R06/AA Ni-MH	2500mAh	12.5hrs
R06/AA Ni-MH	2000mAh	8.0hrs
PP3/9V Ni-MH	250mAh	10hrs

* Charge time stated is for a full charge on fully discharged batteries.